

# A790

# COMM-CO



## Getac A790 Ultra-Rugged Notebook

- 12.1" or 14.1" sunlight readable LCD
- Multiple bays to maximize flexibility and customization
- MIL-STD 810G and IP54 compliant
- Optional MIL-STD 461F compliant
- Thick full magnesium alloy case
- Shock-mounted removable HDD
- Fan-less design
- Optional expansion chassis for PCI & PCIE cards
- Industry's-best 5 year bumper-to-bumper warranty



**Windows®. Life without Walls™. Getac recommends Windows 7.**



### The Getac A790 Ultra-Rugged Notebook

The A790 meets MIL-STD 810G and IP54 standards to survive the harshest environments, and can also satisfy critical EMI requirements with the MIL-STD 461F option. With its sunlight readable 12.1 or 14.1 inch TFT LCD and a shock mounted HDD, the A790 provides a stable platform to perform critical applications in the field. State of the art security options from a TPM chip, fingerprint scanner to a smart card reader provide the highest level of data protection.

The A790 has multiple bays for extensive versatility and expandability. The A790 can be customized to have additional

HDDs for storage, batteries for extended usage time or I/O ports for attaching additional peripheral devices. The A790 is one of the only notebook computers to offer a fully rugged expansion chassis to accommodate ISA, PCI or PCIE cards for specialized applications. The Getac A790 is covered by the industry's-best 5 year bumper-to-bumper warranty.

ProCustom options have included rugged MIL-Connectors and fiber-optic ports making the A790 configurations virtually limitless.

The A790, with its rugged design and powerful software tools, is built to handle the task wherever your job takes.

# Getac A790

## Specifications

information@groupmobile.com  
www.groupmobile.com  
866-784-4338

Group Mobile  
5505 W. Chandler Blvd. Ste. 21  
Chandler, AZ 85226

<b>Ruggedness</b>	Ultra rugged MIL-STD 810G and IP54 Compliant Optional MIL-STD 461F compliant
<b>Operating System</b>	Genuine Windows 7 Genuine Windows Vista® Business Genuine Windows® XP Professional
<b>CPU</b>	Intel® Core™ Duo L2400 1.66GHz processor or Intel® Core™2 Duo L7400 1.5GHz processor 667 MHz FSB 2MB or 4MB L2 cache
<b>Memory</b>	2GB DDR2 expandable to 4GB*
<b>Storage</b>	SATA 160GB HDD; optional 320GB**
<b>VGA Controller</b>	Intel® 945GM 128MB shared memory
<b>Display</b>	12.1" XGA (1024 x 768) TFT sunlight readable display LCD Optional touchscreen or 14.1" XGA (1024 x 768) TFT sunlight readable display LCD Optional touchscreen
<b>Keyboard</b>	Waterproof rubber keyboard Optional backlit waterproof rubber keyboard
<b>X Bay Options</b>	RS-232/RS-422 Ultra-320 SCSI 2nd PCMCIA (Type II x 2 or Type III x 1) Floppy disk drive Smart card reader Bluetooth (V2.0+EDR class 2) GPS (with mouse type antenna)
<b>Media Bay Options</b>	Super multi DVD 2nd battery 2nd HDD 120 GB (IDE)
<b>Expansion Slot</b>	PCMCIA Type II x 2 or Type III x 1

<b>Security</b>	Optional fingerprint scanner TPM 1.2 & Cable lock slot
<b>Communications</b>	10/100/1000 base-T Ethernet 56K ITU V.92 modem WLAN 802.11 a/b/g/n - option GPS (with external antenna) - option Bluetooth® (V2.0+EDR class 2) - option 3G: EV-DO/GSM/GPRS/EDGE/ UMTS/WCDMA/HSDPA - option
<b>Power</b>	AC adapter (90W, 100-240V, 50/60Hz) Li-Ion smart battery (7800mAh) Media bay 2nd Li-Ion battery (5200mAh) - option X bay 3rd Li-Ion battery (5200mAh) - option
<b>Dimensions and Weight</b>	12.1" display - 13.1" x 10.5" x 3.4" (332.2 x 267 x 85.4 mm) 12.6 lbs (5.8 kg)*** or 14.1" display - 13.1" x 11.0" x 3.4" (332.2 x 279 x 85.4 mm) 13.0 lbs (5.9 kg)***
<b>Temperature</b>	Operating temp: 32°F to 140°F / 0°C to 60°C (Optional low temperature: -4°F/-20°C) Storage temp: -40°F to 158°F (-40°C to 70°C) Humidity: 5% to 95% RH, non-condensing
<b>I/O Interfaces</b>	DC in x 1 USB 2.0 x 2 Docking port x 1 Parallel port (DB-25) x 1 Serial port (RS-232) x 1 Network (RJ-45) x 1 Modem (RJ-11) x 1 External VGA x 1 IrDA x 1 IEEE 1394b x 1 Audio output x 1 Microphone x 1 Speakers x 2
<b>Expansion Chassis</b>	Optional PCI or PCI-E expansion chassis
<b>Warranty</b>	5 Year bumper-to-bumper warranty standard†

**Company Info:** **Tel: 31114-370030** **www.atexshop.com**  
**Comm-Co** **Fax: +31114-370029** **www.ruggedshop.nl**  
**Kreekzoom 9** **E-mail: Info@comm-co.com** **www.webpainter.nl**  
**4561 GX Hulst** **Website: http://www.comm-co.com** **www.wavecomblog.com**  
**The Netherlands** **Webshop: http://www.ecommshop.com** **www.eyecctv.nl**